



HOSHIZAKI

All Hoshizaki Co., Ltd factories are
ISO9001 and **ISO14001** registered

ISO9001

Hoshizaki Co., Ltd Factories

Registration Number JET-0205
Registration Date 9th August 1999

ISO14001

Hoshizaki Co., Ltd Factories

Registration Number E01-204
Registration Date 25th July 2001



The Hoshizaki Group is actively working
to preserve the Environment or solve
social issue through its Business.

Scan for
more details



HOSHIZAKI

FOR YOUR KITCHEN



Official partner with Koryaiko Philippine Inc

WHAT'S

4 ABOUT



5 ICE MAKER

- 6-7** Cube Ice
- 8-10** Crescent Ice
- 10-11** Nugget / Flake Ice
- 11-12** Dice / Half Dice Ice
- 12** Special Ice



13 ICE STORAGE BIN

- 13** Ice Storage Bin Compatability & Specifications
- 14** Ice Dispenser
- 15** Ice Maker Specifications



16 REFRIGERATION

- 17-19** A-Fit Upright Model
- 19** A-Fit Upright Specifications
- 20-24** A-Fit Undercounter Model
- 25** A-Fit Undercounter Specifications
- 26-28** A-Fit Pillar-less Model
- 28** A-Fit Pillar-less Specifications
- 29-32** A-Fit Glass Model
- 33** A-Fit Prep Table Model
- 34** A-Fit Glass Specifications
- 34** A-Fit Prep Table Specifications
- 35-36** Goldline Model
- 37** Goldline Specifications



38 DEEP FREEZER

- 38** Deep Freezer Specifications



39-40 DISHWASHER

- 40** Dishwasher Specifications
- 41** Beer Dispenser
- 41** Beer Dispenser Specifications

INSIDE?



Hoshizaki is a global leading manufacturer of commercial equipment for food and beverage services that was founded in Nagoya, Japan in 1947, and began operations in Toyoake factory in 1956.

We have continually manufactured and offered a wide variety of high-quality products, in order to meet changing needs and demands, since Hoshizaki's establishment. In particular, we provide equipment, such as ice machines, commercial refrigeration, beverage dispensers, and dishwashers.

Hoshizaki has a comprehensive global network with its manufacturing plants in the United States, the United Kingdom, Denmark, Turkey, Mexico, China, India, Australia, and Brazil. We also have sales and after-sales service teams globally, and our products that incorporate creativity and innovation are highly valued, supporting various dining scenes for worldwide customers.




ICE MAKER

Together with the vision to prioritize the customer satisfaction, Hoshizaki has invented the original technology for the Basic Designs of Evaporators. As the result, some Hoshizaki Ice Machine products use the **Stainless Steel Evaporator** which produce the best quality ice that is already proven melt very slowly (up to 24 hours time) compared to any other ice produced by different ice machines brand.




CUBE STANDARD



MODEL	IM-30CA	IM-45CA	IM-45CNS
Dimension WxDxH (+ Leg)	398 x 510 x 695 (+150) mm	660 x 570 x 695 (+150) mm	633 x 511 x 690 (+90) mm
Electrical Consumption	250 W	344 W	360 W
Ice Production Per 24h (approx.)	27 kg (AT21°C / WT15°C) 21 kg (AT32°C / WT21°C)	45 kg (AT21°C / WT15°C) 39 kg (AT32°C / WT21°C)	40 kg (AT21°C / WT15°C) 36 kg (AT32°C / WT21°C)
Ice Production Per Cycle (approx.)	0.4 kg / 18 pcs	0.67 kg / 30 pcs	0.67 kg / 30 pcs
Storage Capacity (approx.)	12 kg	15 kg	15 kg

CUBE STANDARD




MODEL	IM-65A	IM-65NS	IM-100A
Dimension WxDxH (+ Leg)	660 x 570 x 800 (+150) mm	633 x 506 x 840 (+90) mm	660 x 570 x 1200 (+150) mm
Electrical Consumption	430 W	370 W	680 W
Ice Production Per 24h (approx.)	67 kg (AT21°C / WT15°C) 59 kg (AT32°C / WT21°C)	58 kg (AT21°C / WT15°C) 47 kg (AT32°C / WT21°C)	108 kg (AT21°C / WT15°C) 88 kg (AT32°C / WT21°C)
Ice Production Per Cycle (approx.)	0.94 kg / 42 pcs	0.94 kg / 42 pcs	1.8 kg / 80 pcs
Storage Capacity (approx.)	26 kg	26 kg	52 kg

CUBE STANDARD




MODEL	IM-100NS	IM-100CNS	IM-130A
Dimension WxDxH	704 x 506 x 1200 (+90) mm	1004 x 600 x 700 (+90) mm	660 x 570 x 1200 (+150) mm
Electrical Consumption	650 W	650 W	820 W
Ice Production Per 24h (approx.)	93 kg (AT21°C / WT15°C) 83 kg (AT32°C / WT21°C)	93 kg (AT21°C / WT15°C) 83 kg (AT32°C / WT21°C)	126 kg (AT21°C / WT15°C) 108 kg (AT32°C / WT21°C)
Ice Production Per Cycle (approx.)	1.8 kg / 80pcs	1.8 kg / 80 pcs	1.8 kg / 80 pcs
Storage Capacity (approx.)	50 kg	38 kg	52 kg

CUBE STANDARD




MODEL	IM-220AA-B-301SA	IM-240ANE-B-301SA	IM-240DNS-B-801SA
Dimension WxDxH	560 x 820 x 1796(+90)mm	560 x 820 x 1901(+90) mm	1219 x 820 x 1521 (+90) mm
Electrical Consumption	1068 W	1320 W	1250 W
Ice Production Per 24h (approx.)	210 kg (AT21°C / WT15°C) 180 kg (AT32°C / WT21°C)	220 kg (AT21°C / WT15°C) 195 kg (AT32°C / WT21°C)	220 kg (AT21°C / WT15°C) 195 kg (AT32°C / WT21°C)
Ice Production Per Cycle (approx.)	3.2 kg / 140 pcs	3.2 kg / 140 pcs	3.2 kg / 140 pcs
Storage Capacity (approx.)	144k kg	144 kg	348 kg

CUBE STANDARD




MODEL	IM-240DNS-STCR	IM-440AA-B-801SA	IM-480DNS-B-801SA
Dimension WxDxH	1084 x 710 x 1657 (+150) mm	1219 x 820 x 1796 (+90) mm	1219 x 820 x 2006 (+90) mm
Electrical Consumption	IM-240DNE: 1250 W P-200CR4: 253 W	2136 W	2500 W
Ice Production Per 24h (approx.)	220 kg (AT21°C / WT15°C) 195 kg (AT32°C / WT21°C)	420 kg (AT21°C / WT15°C) 360 kg (AT32°C / WT21°C)	440 kg (AT21°C / WT15°C) 405 kg (AT32°C / WT21°C)
Ice Production Per Cycle (approx.)	3.2 kg / 140 pcs	6.4 kg / 280 pcs	6.4 kg / 280 pcs
Storage Capacity (approx.)	P-200CR4(Cube): 160KG ST-200A(Crushed): 135KG	348 kg	348 kg

CUBE STANDARD IM-480DNE




MODEL	IM-480DNS-STCR	IM-480DNS-STCRN
Dimension WxDxH(+Leg)	1084 x 710 x 2142 (+150) mm	1084 x 710 x 2527 (+150) mm
Electrical Consumption	IM-480DNE: 2500W P-200CR4: 253W	IM-480DNE: 2500W P-200CR4: 253W
Ice Production Per 24h (approx.)	440 kg (AT21°C / WT15°C) 405 kg (AT32°C / WT21°C)	440 kg (AT21°C / WT15°C) 405 kg (AT32°C / WT21°C)
Ice Production Per Cycle (approx.)	6.4 kg / 280 pcs	6.4 kg / 280 pcs
Storage Capacity (approx.)	P-200CR4(Cube): 160 kg ST-200A(Crushed): 135 kg	P-200CR4(Cube): 255 kg ST-200A(Crushed): 135 kg

CRESCENT




MODEL	KM-40C	KM-60C	KM-80C
Dimension WxDxH(+Leg)	452 x 610 x 838 (+150) mm	605 x 610 x 838 (+150) mm	605 x 712 x 838 (+150) mm
Electrical Consumption	222 W	335 W	464 W
Ice Production Per 24h (approx.)	36 kg (AT21°C / WT15°C) 29 kg (AT32°C / WT21°C)	59 kg (AT21°C / WT15°C) 54 kg (AT32°C / WT21°C)	78 kg (AT21°C / WT15°C) 63 kg (AT32°C / WT21°C)
Ice Production Per Cycle (approx.)	0.74 kg / 80 pcs	1.00 kg / 110 pcs	1.16 kg / 130 pcs
Storage Capacity (approx.)	16 kg	23 kg	34 kg

CRESCENT



CRESCENT


With Fully
Automated Cleaning



MODEL	KM-130C	KM-40C-W
Dimension WxDxH(+Leg)	630 x 719 x 1194 (+150) mm	452 x 610 x 838 (+150) mm
Electrical Consumption	632 W	222 W
Ice Production Per 24h (approx.)	125 kg (AT21°C / WT15°C) 100 kg (AT32°C / WT21°C)	36 kg (AT21°C / WT15°C) 29 kg (AT32°C / WT21°C)
Ice Production Per Cycle (approx.)	1.86 kg / 208 pcs	0.74 kg / 80 pcs
Storage Capacity (approx.)	55 kg	16 kg

CRESCENT


With Fully
Automated Cleaning



MODEL	KM-60C-W	KM-80C-W	KM-130C-W
Dimension WxDxH(+Leg)	605 x 610 x 838 (+150) mm	605 x 712 x 838 (+150) mm	630 x 719 x 1194 (+150) mm
Electrical Consumption	335 W	464 W	632 W
Ice Production Per 24h (approx.)	59 kg (AT21°C / WT15°C) 54 kg (AT32°C / WT21°C)	78 kg (AT21°C / WT15°C) 63 kg (AT32°C / WT21°C)	125 kg (AT21°C / WT15°C) 100 kg (AT32°C / WT21°C)
Ice Production Per Cycle (approx.)	1.00 kg / 110 pcs	1.16 kg / 130 pcs	1.86 kg / 208 pcs
Storage Capacity (approx.)	23 kg	34 kg	55 kg

CRESCENT


With UV LED




MODEL	KM-40C-U	KM-60C-U	KM-80C-U
Dimension WxDxH(+Leg)	452 x 610 x 838 (+150) mm	605 x 610 x 838 (+150) mm	605 x 712 x 838 (+150) mm
Electrical Consumption	222 W	335 W	464 W
Ice Production Per 24h (approx.)	36 kg (AT21°C / WT15°C) 29 kg (AT32°C / WT21°C)	59 kg (AT21°C / WT15°C) 54 kg (AT32°C / WT21°C)	78 kg (AT21°C / WT15°C) 63 kg (AT32°C / WT21°C)
Ice Production Per Cycle (approx.)	0.74 kg / 80 pcs	1.00 kg / 110 pcs	1.16 kg / 130 pcs
Storage Capacity (approx.)	16 kg	23 kg	34 kg

CRESCENT

With UV LED




CRESCENT




MODEL	KM-130C-U	KMD-201AB-B-301SA
Dimension WxDxH(+Leg)	630 x 719 x 1194 (+150) mm	560 x 820 x 1631(+90)mm
Electrical Consumption	632 W	806 W
Ice Production Per 24h (approx.)	125 kg (AT21°C / WT15°C) 100 kg (AT32°C / WT21°C)	190 kg (AT21°C / WT15°C) 160 kg (AT32°C / WT21°C)
Ice Production Per Cycle (approx.)	1.86 kg / 208 pcs	3.7kg / 416pcs
Storage Capacity (approx.)	55 kg	144 kg


CRESCENT




MODEL	KMD-270AB-B-301SA	KMD-400AB-B-801SA	KMD-540AB-B-801SA
Dimension WxDxH(+Leg)	560 x 820 x 1631(+90)mm	1219 x 820 x 1631(+90)mm	1219 x 820 x 1631(+90)mm
Electrical Consumption	1114 W	1612 W	2228 W
Ice Production Per 24h (approx.)	260 kg (AT21°C / WT15°C) 230 kg (AT32°C / WT21°C)	380 kg (AT21°C / WT15°C) 320 kg (AT32°C / WT21°C)	520 kg (AT21°C / WT15°C) 460 kg (AT32°C / WT21°C)
Ice Production Per Cycle (approx.)	5.3kg / 572pcs	7.4kg / 832pcs	10.8kg / 1144pcs
Storage Capacity (approx.)	144 kg	348 kg	348 kg

CRESCENT



MODEL	KM-470AJ-B-501SA	KM-590DJ-B-801SA	KM-1180DJ-B-801SA
Dimension WxDxH (+Leg)	762 x 820 x 1846(+90)mm	1219 x 820 x 1846(+90)mm	1219 x 820 x 2411(+90)mm
Electrical Consumption	1910 W	2310 W	4620 W
Ice Production Per 24h (approx.)	490 kg (AT21°C / WT15°C) 390 kg (AT32°C / WT21°C)	650 kg (AT21°C / WT15°C) 575 kg (AT32°C / WT21°C)	1300 kg (AT21°C / WT15°C) 1150 kg (AT32°C / WT21°C)
Ice Production Per Cycle (approx.)	9.7kg / 960pcs	12.9kg / 1440pcs	25.8kg / 2880pcs
Storage Capacity (approx.)	217 kg	348 kg	348kg

NUGGET / FLAKE / CUBELET
NUGGET CM-110KE-50
Compressed Flake Ice

FLAKE FM-120KE



MODEL	FM-120KE	CM-110KE-50
Dimension WxDxH (+Leg)	640 x 640 x 711(+89)mm	940 x 600 x 711(+89)mm
Electrical Consumption	550 W	550 W
Ice Production Per 24h (approx.)	120 kg (AT21°C / WT15°C) 100 kg (AT32°C / WT21°C)	105 kg (AT21°C / WT15°C) 90 kg (AT32°C / WT21°C)
Refrigerant	R290	R290
Storage Capacity (approx.)	26kg	57kg

NUGGET FM-300AKE-N
Compressed Flake Ice

FLAKE FM-300/480AKE-SB



MODEL	FM-300AKE-SB-B-301SA	FM-300AKE-N-SB-B-30SA	FM-480AKE-SB-B-301SA
Dimension WxDxH (+Leg)	560 x 820 x 1801(+90)mm	560 x 820 x 1801(+90)mm	560 x 820 x 1801(+90)mm
Electrical Consumption	1180 W	1200 W	1590 W
Ice Production Per 24h (approx.)	270 kg (AT21°C / WT15°C) 200 kg (AT32°C / WT21°C)	240 kg (AT21°C / WT15°C) 180 kg (AT32°C / WT21°C)	430 kg (AT21°C / WT15°C) 330 kg (AT32°C / WT21°C)
Refrigerant	R404A	R404A	R404A
Storage Capacity (approx.)	144 kg	144 kg	144kg

NUGGET FM-480/600AKE-N
Compressed Flake Ice

FLAKE FM-600AKE


MODEL	FM-480AKE-N-SB-B-30SA	FM-600AKE-SB-B-301SA	FM-600AKE-N-SB-B-30SA
Dimension WxDxH (+Leg)	560 x 820 x 1801(+90)mm	560 x 820 x 1801(+90)mm	560 x 820 x 1801(+90)mm
Electrical Consumption	1590 W	1900 W	1950 W
Ice Production Per 24h (approx.)	370 kg (AT21°C / WT15°C) 280 kg (AT32°C / WT21°C)	540 kg (AT21°C / WT15°C) 445 kg (AT32°C / WT21°C)	460 kg (AT21°C / WT15°C) 400 kg (AT32°C / WT21°C)
Refrigerant	R404A	R404A	R404A
Storage Capacity (approx.)	144kg	144kg	144kg


DICE ICE
DICE


MODEL	SRM-45A	SRM-60A	SRM-105A
Dimension WxDxH (+ Leg)	500 x 580 x 750 mm	660 x 670 x 970 (+80) mm	660 x 670 x 1120 (+80) mm
Electrical Consumption	270 W	450 W	530 W
Ice Production Per 24h (approx.)	41 kg (AT21°C / WT15°C) 34 kg (AT32°C / WT21°C)	60 kg (AT21°C / WT15°C) 50 kg (AT32°C / WT21°C)	95 kg (AT21°C / WT15°C) 78 kg (AT32°C / WT21°C)
Ice Production Per Cycle (approx.)	0.5kg / 55pcs	0.81kg / 80 pcs	1.17kg / 126 pcs
Storage Capacity (approx.)	14 kg	31.4 kg	43.6 kg


DICE


MODEL	SRM-125UB	SRM-270AB-B-501SA
Dimension WxDxH (+ Leg)	660 x 670 x 850 mm	762 x 820 x 1581(+90)mm
Electrical Consumption	653 W	1182 W
Ice Production Per 24h (approx.)	116 kg (AT21°C / WT15°C) 92 kg (AT32°C / WT21°C)	242 kg (AT21°C / WT15°C) 194 kg (AT32°C / WT21°C)
Ice Production Per Cycle (approx.)	1.17kg / 126 pcs	2.41kg / 260pcs
Storage Capacity (approx.)	24 kg	217 kg

DICE SRM-450AB



HALF DICE SRM-270/450AB-14



MODEL	SRM-270AB-14-B-501SA	SRM-450AB-S-B-501SA	SRM-450AB-S-14-B-501SA
Dimension WxDxH (+ Leg)	762 x 820 x 1581(+90)mm	762 x 820 x 1781(+90)mm	762 x 820 x 1781(+90)mm
Electrical Consumption	1219.5 W	1681.6 W	1703.9 W
Ice Production Per 24h (approx.)	229 kg (AT21°C / WT15°C) 183 kg (AT32°C / WT21°C)	403 kg (AT21°C / WT15°C) 318 kg (AT32°C / WT21°C)	408 kg (AT21°C / WT15°C) 344 kg (AT32°C / WT21°C)
Ice Production Per Cycle (approx.)	2.57kg / 320pcs	4.19kg / 440pcs	4.43kg / 544pcs
Storage Capacity (approx.)	217kg	217kg	217kg

SPECIAL ICE

BALL












MODEL	IM-65NS-Q
Dimension WxDxH (+ Leg)	633 x 506 x 860(+90)mm
Electrical Consumption	370 W
Ice Production Per 24h (approx.)	25 kg (AT21°C / WT15°C) 20 kg (AT32°C / WT21°C)
Ice Production Per Cycle (approx.)	0.67kg / 15pcs
Storage Capacity (approx.)	17kg



MODEL	B-301SA	B-501SA	B-801SA
Dimension WxDxH (+ Leg)	558.8 x 820 x 1016 (+90) mm	762 x 820 x 1016 (+90) mm	1219.2 x 820 x 1016 (+90) mm
Door Style	Upward Opening	Upward Opening	Upward Opening
Scoop	1	1	1
Effective Capacity (approx.)	144 kg	217 kg	348 kg
Weight Gross	49 kg	57 kg	86 kg

ICE STORAGE BIN COMPATABILITY

ICE MACHINE \ ICE BIN	IM-240A FM-300 FM-480 FM-600	IM-220 KMD-201 KMD-270	KM-470 FM-750 SRM-270 SRM-450	IM-240A x 2 FM-300 X 2 FM-480 x 2 FM-600 X 2	IM-220x 2 KMD-201 x 2 KMD-270 x 2	KM-590	IM-240D IM-240X
B-301SA  Top Kit	 22	 No Top Kit					
B-501SA  Top Kit	 22+ 8D	 8D	 30				
B-801SA  Top Kit	 22+ 8D + 18D	 8D + 18D	 30 + 18D	 22 + 22 + 4DM	 4DM + 4DR	 No Top Kit	 IMD2

ICE STORAGE BIN SPECIFICATIONS


Model Name	Storage Capacity (kg)	Product Dimension (mm)	Packing Dimension (mm)	Net / Gross Weight
B-301SA	188 / 144	558.8 x 820 x 1016 ~ 1106	670 x 920 x 1190	37 / 49
B-501SA	173 / 217	760 x 820 x 1016 ~ 1106	900 x 940 x 1190	47 / 62
B-801SA	286 / 348	1219.2 x 820 x 1106 ~ 1136	1360 x 940 x 1190	64 / 86

ICE DISPENSER

Cold drinks are very much favoured especially in casual or self-service environments; operators can lessen the work or manpower with an ice dispersing machine. Hozshizaki's cubelet ice dispensers meet the need with its 2-in-1 function that makes and provides ice to customers through its compact and space saving dispensers.



CUBELET Compressed Flake Ice



MODEL	DCM-60KE	DCM-120KE
Dimension WxDxH (+ Leg)	350 x 585 x 645 (+50 ~ 65) mm	350 x 585 x 765 (+50~65) mm
Electrical Consumption	320 W	560 W
Ice Production Per 24h (approx.)	50 kg (AT21°C / WT15°C) 38 kg (AT32°C / WT21°C)	105 kg (AT21°C / WT15°C) 85 kg (AT32°C / WT21°C)
Ice Production 40gm Cup (approx.)	73 cups / 30min (AT21°C / WT15°C) 67 cups / 30min (AT32°C / WT15°C)	154 cups / 30min (AT21°C / WT15°C) 144 cups / 30min (AT32°C / WT15°C)
Storage Capacity (approx.)	1.9 kg	4.0 kg

ICE MAKER SPECIFICATIONS

Category	Ice Shape	Model Name	Self-Contained / Modular - Type	Production Capacity (kg / day)		Bin Capacity (Approx. kg)	Compatible Bins	Product Dimension (mm)	Packing Dimension (mm)	Net / Gross Weight (kg)
				AT.21°C, WT.15°C	AT.32°C, WT.21°C			W x D x H (+ Leg)	W x D x H	
IM	Cube - Standard	IM-30CA	Self-Contained	27	21	12	NA	398 x 510 x 695 (+150)	490 x 610 x 870	39 / 49
IM	Cube - Standard	IM-45CA	Self-Contained	45	39	15	NA	660 x 570 x 695 (+150)	760 x 680 x 870	52 / 65
IM	Cube - Standard	IM-45CNS	Self-Contained	40	36	15	NA	633 x 511 x 690 (+90)	735 x 570 x 864	48 / 56
IM	Cube - Standard	IM-65A	Self-Contained	67	59	26	NA	660 x 570 x 800 (+150)	760 x 680 x 970	60 / 74
IM	Cube - Standard	IM-65NS	Self-Contained	58	47	26	NA	633 x 506 x 840 (+90)	735 x 570 x 1012	53 / 61
IM	Cube - Standard	IM-100A	Self-Contained	110	95	52	NA	660 x 570 x 1200 (+150)	760 x 680 x 1379	76 / 95
IM	Cube - Standard	IM-100NS	Self-Contained	93	83	52	NA	704 x 506 x 1200 (+90)	805 x 580 x 1375	76 / 85
IM	Cube - Standard	IM-100CNS	Self-Contained	93	83	38	NA	1004 x 600 x 700 (+150)	1110 x 700 x 875	77 / 88
IM	Cube - Standard	IM-130A	Self-Contained	126	108	52	NA	660 x 570 x 1200 (+150)	760 x 680 x 1379	79 / 98
IM	Cube - Standard	IM-220AA	Modular	210	180	NA		560 x 639 x 775	644 x 728 x 878	69 / 76
IM	Cube - Standard	IM-240ANE	Modular	220	195	Various		560 x 700 x 880	665 x 820 x 1054	80 / 95
IM	Cube - Standard	IM-240DNS	Modular	220	195	Various		1084 x 700 x 500	1196 x 825 x 640	88 / 101
IM	Cube - Standard	IM-240XNS	Modular	220	210	Various		1084 x 697 x 485	1196 x 825 x 640	84 / 98
KM	Crescent	KM-40C-(W/U)	Self-Contained	36	29	16	NA	452 x 610 x 838 (+150)	555 x 715 x 953	40 / 50
KM	Crescent	KM-60C-(W/U)	Self-Contained	59	54	23	NA	605 x 610 x 838 (+150)	710 x 715 x 953	46 / 58
KM	Crescent	KM-80C-(W/U)	Self-Contained	78	63	34	NA	605 x 712 x 838 (+150)	700 x 805 x 953	51 / 64
KM	Crescent	KM-130C-(W/U)	Self-Contained	125	100	55	NA	630 x 719 x 1194 (+150)	725 x 825 x 1351	69 / 81
KMD	Crescent	KMD-201AB	Modular	190	160	Various		560 x 625 x 610	668 x 727 x 783	57 / 73
KMD	Crescent	KMD-270AB	Modular	260	230	Various		560 x 625 x 610	668 x 727 x 783	57 / 73
KM	Crescent	KM-470AJ	Modular	490	390	Various		762 x 695 x 825	855 x 843 x 983	122 / 136
KM	Crescent	KM-590DJ	Modular	650	575	Various		1219 x 695 x 695	1312 x 843 x 855	136 / 154
FM	Flake	FM-120KE	Self-Contained	120	100	26	NA	640 x 600 x 711 (+89)	746 x 706 x 887	66 / 76
FM	Flake	CM-100KE-50	Self-Contained	105	90	57	NA	940 x 600 x 711 (+89)	1046 x 706 x 887	76 / 88
FM	Flake	FM-300AKE-SB	Modular	270	200	Various		560 x 700 x 780	665 x 820 x 950	80 / 87
FM	Nugget	FM-300AKE-N-SB	Modular	240	180	Various		560 x 700 x 780	665 x 820 x 950	80 / 87
FM	Flake	FM-480AKE-SB	Modular	430	330	Various		560 x 700 x 780	665 x 820 x 950	95 / 102
FM	Nugget	FM-480AKE-N-SB	Modular	370	280	Various		560 x 700 x 780	665 x 820 x 950	95 / 102
FM	Flake	FM-600AKE-SB	Modular	540	445	Various		560 x 700 x 780	665 x 820 x 950	107 / 114
FM	Nugget	FM-600AKE-N-SB	Modular	460	400	Various		560 x 700 x 780	665 x 820 x 950	107 / 114
SRM	Dice	SRM-45A	Self-Contained	41	34	14	NA	500 x 580 x 750	625 x 716 x 875	36 / 40
SRM	Dice	SRM-60A	Self-Contained	60	54	31.4	NA	660 x 670 x 970 (+80)	785 x 860 x 1100	58 / 65
SRM	Dice	SRM-105A	Self-Contained	95	78	43.6	NA	660 x 670 x 1120 (+80)	785 x 860 x 1250	61 / 69
SRM	Dice	SRM-125UB	Self-Contained	116	92	24	NA	660 x 670 x 850	780 x 850 x 1050	58 / 75
SRM	Dice	SRM-270AB	Modular	242	194	Various		760 x 620 x 560	850 x 710 x 750	59 / 78
SRM	Half Dice	SRM-270AB-14	Modular	229	183	Various		760 x 620 x 560	850 x 710 x 750	59 / 78
SRM	Dice	SRM-450AB-S	Modular	403	318	Various		760 x 620 x 760	865 x 720 x 945	84 / 101
SRM	Half Dice	SRM-450AB-S-14	Modular	408	344	Various		760 x 620 x 760	865 x 720 x 945	84 / 101
Special	Sphere	IM-65NS-Q	Self-Contained	25	20	17	NA	633 x 506 x 860 (+90)	735 x 570 x 1012	53 / 66
DCM	Dispenser	DCM-60KE	Self-Contained	50	38	1.9	NA	350 x 585 x 645 (+50~65)	440 x 655 x 906	47 / 56
DCM	Dispenser	DCM-120KE	Self-Contained	105	85	4	NA	350 x 585 x 765 (+50~65)	440 x 655 x 1026	57 / 66



As our mission and plan to achieve and maintain optimum your satisfaction, we proudly introduce our technology based on years of researching and innovating for better quality of Chillers and Freezers: **A-Fit Technology.**

Upright Refrigerator

			
MODEL	HR-78MA-P	HR-128MA-P	HR-148MA-P
Dimension WxDxH	700 x 800 x 2050 mm	1200 x 800 x 2050 mm	1400 x 800 x 2050 mm
Electrical Consumption	238 W	333 W	367 W
Temperature Control	-6°C ~ 12°C	-6°C ~ 12°C	-6°C ~ 12°C
Number of Shelves	4	8	8
Effective Capacity	569 L	1053 L	1243 L

		
MODEL	HR-188MA-P	HR-76MA-P
Dimension WxDxH	1800 x 800 x 2050 mm	700 x 650 x 2050 mm
Electrical Consumption	413 W	283 W
Temperature Control	-6°C ~ 12°C	-6°C ~ 12°C
Number of Shelves	12	4
Effective Capacity	1632 L	467 L

		
MODEL	HR-126MA-P	HR-146MA-P
Dimension WxDxH	1200 x 650 x 2050 mm	1400 x 650 x 2050 mm
Electrical Consumption	305 W	309 W
Temperature Control	-6°C ~ 12°C	-6°C ~ 12°C
Number of Shelves	8	8
Effective Capacity	866 L	982 L

Upright Freezer



MODEL **HF-78MA-P**

Dimension WxDxH	700 x 800 x 2050 mm
Electrical Consumption	469 W
Temperature Control	-23°C ~ -7°C
Number of Shelves	4
Effective Capacity	569 L



MODEL **HF-128MA-P**

Dimension WxDxH	1200 x 800 x 2050 mm
Electrical Consumption	700 W
Temperature Control	-23°C ~ -7°C
Number of Shelves	8
Effective Capacity	1047 L



MODEL **HF-148MA-P**

Dimension WxDxH	1400 x 800 x 2050 mm
Electrical Consumption	740 W
Temperature Control	-23°C ~ -7°C
Number of Shelves	8
Effective Capacity	1233 L



MODEL **HF-188MA-P**

Dimension WxDxH	1800 x 800 x 2050 mm
Electrical Consumption	917 W
Temperature Control	-23°C ~ -7°C
Number of Shelves	12
Effective Capacity	1622 L



MODEL **HF-76MA-P**

Dimension WxDxH	700 x 650 x 2050 mm
Electrical Consumption	316 W
Temperature Control	-23°C ~ -7°C
Number of Shelves	4
Effective Capacity	467 L



MODEL **HF-126MA-P**

Dimension WxDxH	1200 x 650 x 2050 mm
Electrical Consumption	346 W
Temperature Control	-23°C ~ -7°C
Number of Shelves	8
Effective Capacity	866 L



MODEL **HF-146MA-P**

Dimension WxDxH	1400 x 650 x 2050 mm
Electrical Consumption	482 W
Temperature Control	-23°C ~ -7°C
Number of Shelves	8
Effective Capacity	1011 L

Upright Dual Temp.



MODEL **HRF-78MB-P**

Dimension WxDxH	700 x 800 x 2050 mm
Electrical Consumption	365 W
Refrigerator Temperature Control	-2°C ~ 12°C
Freezer Temperature Control	-23°C ~ -11°C
Number of Shelves	4
Effective Capacity	448 L (Refrigerator: 234 L, Freezer: 214 L)



MODEL **HRF-128MA-P**

Dimension WxDxH	1200 x 800 x 2050 mm
Electrical Consumption	704 W
Refrigerator Temperature Control	-6°C ~ 12°C
Freezer Temperature Control	-23°C ~ -7°C
Number of Shelves	8
Effective Capacity	908 L (Refrigerator: 454 L, Freezer: 454 L)



MODEL **HRF-148MA-P**

Dimension WxDxH	1400 x 800 x 2050 mm
Electrical Consumption	808 W
Refrigerator Temperature Control	-6°C ~ 12°C
Freezer Temperature Control	-23°C ~ -7°C
Number of Shelves	8
Effective Capacity	1110 L (Refrigerator: 550 L, Freezer: 550 L)



MODEL **HRF-188MA-P**

Dimension WxDxH	1800 x 800 x 2050 mm
Electrical Consumption	844 W
Refrigerator Temperature Control	-6°C ~ 12°C
Freezer Temperature Control	-23°C ~ -7°C
Number of Shelves	12
Effective Capacity	1523 L (Refrigerator: 1025 L, Freezer: 498 L)

A-FIT UPRIGHT SPECIFICATIONS

Category	Product Group	Model Name	Effective Capacity		No. of Shelves	Temperature Control		Electric Consumption	Product Dimension (mm) W x D x H
			Refrigerator	Freezer		Refrigerator	Freezer		
A-fit	Upright	HR-78MA-P	569 L	-	4	-6°C to 12°C	-	238 W	700 x 800 x 2050
A-fit	Upright	HR-128MA-P	1053 L	-	8	-6°C to 12°C	-	333 W	1200 x 800 x 2050
A-fit	Upright	HR-148MA-P	1243 L	-	8	-6°C to 12°C	-	367 W	1400 x 800 x 2050
A-fit	Upright	HR-188MA-P	1632 L	-	12	-6°C to 12°C	-	413 W	1800 x 800 x 2050
A-fit	Upright	HR-76MA-P	467 L	-	4	-6°C to 12°C	-	283 W	700 x 650 x 2050
A-fit	Upright	HR-126MA-P	866 L	-	8	-6°C to 12°C	-	305 W	1200 x 650 x 2050
A-fit	Upright	HR-146MA-P	982 L	-	8	-6°C to 12°C	-	309 W	1400 x 650 x 2050
A-fit	Upright	HF-78MA-P	569 L	-	4	-	-23°C to -7°C	469 W	700 x 800 x 2050
A-fit	Upright	HF-128MA-P	1047 L	-	8	-	-23°C to -7°C	700 W	1200 x 800 x 2050
A-fit	Upright	HF-148MA-P	1233 L	-	8	-	-23°C to -7°C	740 W	1400 x 800 x 2050
A-fit	Upright	HF-188MA-P	1622 L	-	12	-	-23°C to -7°C	917 W	1800 x 800 x 2050
A-fit	Upright	HF-76MA-P	467 L	-	4	-	-23°C to -7°C	316 W	700 x 650 x 2050
A-fit	Upright	HF-126MA-P	866 L	-	8	-	-23°C to -7°C	346 W	1200 x 650 x 2050
A-fit	Upright	HF-146MA-P	1011 L	-	8	-	-23°C to -7°C	482 W	1400 x 650 x 2050

A-FIT DUAL TEMP. SPECIFICATIONS

Category	Model Name	Effective Capacity		No. of Shelves	Temperature Control		Electric Consumption	Product Dimension (mm) W x D x H
		Refrigerator	Freezer		Refrigerator	Freezer		
Dual Temp.	HRF-78MB-P	234 L	214 L	4	-2°C to 12°C	-23°C to -11°C	365 W	700 x 800 x 2050
Dual Temp.	HRF-128MA-P	454 L	454 L	8	-6°C to 12°C	-23°C to -7°C	704 W	1200 x 800 x 2050
Dual Temp.	HRF-148MA-P	550 L	550 L	8	-6°C to 12°C	-23°C to -7°C	808 W	1400 x 800 x 2050
Dual Temp.	HRF-188MA-P	1025 L	498 L	12	-6°C to 12°C	-23°C to -7°C	844 W	1800 x 800 x 2050

Undercounter Refrigerator



MODEL RT-96MA-P

Dimension WxDxH	900 x 600 x 850 mm
Electrical Consumption	240 W
Temperature Control	-6°C ~ 12°C
Number of Shelves	2
Effective Capacity	151 L



MODEL RT-126MA-P

Dimension WxDxH	1200 x 600 x 850 mm
Electrical Consumption	245 W
Temperature Control	-6°C ~ 12°C
Number of Shelves	4
Effective Capacity	231 L



MODEL RT-156MA-P

Dimension WxDxH	1500 x 600 x 850 mm
Electrical Consumption	260 W
Temperature Control	-6°C ~ 12°C
Number of Shelves	4
Effective Capacity	318 L



MODEL RT-186MA-P

Dimension WxDxH	1800 x 600 x 850 mm
Electrical Consumption	280 W
Temperature Control	-6°C ~ 12°C
Number of Shelves	6
Effective Capacity	401 L



MODEL RT-98MA-P

Dimension WxDxH	900 x 750 x 850 mm
Electrical Consumption	240 W
Temperature Control	-6°C ~ 12°C
Number of Shelves	2
Effective Capacity	199 L



MODEL RT-128MA-P

Dimension WxDxH	1200 x 750 x 850 mm
Electrical Consumption	245 W
Temperature Control	-6°C ~ 12°C
Number of Shelves	4
Effective Capacity	307 L



MODEL RT-158MA-P

Dimension WxDxH	1500 x 750 x 850 mm
Electrical Consumption	260 W
Chiller Temperature Control	-6°C ~ 12°C
Number of Shelves	4
Effective Capacity	420 L



MODEL RT-188MA-P

Dimension WxDxH	1800 x 750 x 850 mm
Electrical Consumption	280 W
Chiller Temperature Control	-6°C ~ 12°C
Number of Shelves	6
Effective Capacity	502 L

Undercounter Low Drawer Refrigerator - Depth 750mm



MODEL RTL-108MA-PD

Dimension WxDxH	980 x 750 x 570 mm
Electrical Consumption	234 W
Chiller Temperature Control	-6°C ~ 12°C
Number of Drawers	2
Effective Capacity	85 L



MODEL RTL-148MA-PD

Dimension WxDxH	1400 x 750 x 570 mm
Electrical Consumption	250 W
Chiller Temperature Control	-6°C ~ 12°C
Number of Drawers	4
Effective Capacity	176 L



MODEL RTL-188MA-PD

Dimension WxDxH	1820 x 750 x 570 mm
Electrical Consumption	260 W
Chiller Temperature Control	-6°C ~ 12°C
Number of Drawers	6
Effective Capacity	267 L

Undercounter Door + Drawer Refrigerator



MODEL RT-126MA-P-3D

Dimension WxDxH	1200 x 600 x 850 mm
Electrical Consumption	245 W
Chiller Temperature Control	-6°C ~ 12°C
Number of Shelves	2
Number of Drawers	3
Effective Capacity	231 L



MODEL RT-156MA-P-3D

Dimension WxDxH	1500 x 600 x 850 mm
Electrical Consumption	260 W
Chiller Temperature Control	-6°C ~ 12°C
Number of Shelves	2
Number of Drawers	3
Effective Capacity	318 L



MODEL	RT-186MA-P-3D	RT-128MA-P-3D
Dimension WxDxH	1800 x 600 x 850 mm	1200 x 750 x 850 mm
Electrical Consumption	280 W	245 W
Chiller Temperature Control	-6°C ~ 12°C	-6°C ~ 12°C
Number of Shelves	4	2
Number of Drawers	3	3
Effective Capacity	401 L	307 L



MODEL	RT-158MA-P-3D	RT-188MA-P-3D
Dimension WxDxH	1500 x 750 x 1076 mm	1800 x 750 x 850 mm
Electrical Consumption	260 W	280 W
Chiller Temperature Control	-6°C ~ 12°C	-6°C ~ 12°C
Number of Shelves	2	4
Number of Drawers	3	3
Effective Capacity	420 L	502 L

Undercounter Freezer



MODEL	FT-96MA-P	FT-126MA-P
Dimension WxDxH	900 x 600 x 850 mm	1200 x 600 x 850 mm
Electrical Consumption	415 W	410 W
Freezer Temperature Control	-23°C ~ -7°C	-23°C ~ -7°C
Number of Shelves	2	4
Effective Capacity	151 L	231 L



MODEL	FT-156MA-P	FT-186MA-P	FT-98MA-P
Dimension WxDxH	1500 x 600 x 850 mm	1800 x 600 x 850 mm	900 x 750 x 850 mm
Electrical Consumption	415 W	400 W	420 W
Freezer Temperature Control	-23°C ~ -7°C	-23°C ~ -7°C	-23°C ~ -7°C
Number of Shelves	4	6	2
Effective Capacity	318 L	401 L	199 L



MODEL	FT-128MA-P	FT-158MA-P	FT-188MA-P
Dimension WxDxH	1200 x 750 x 850 mm	1500 x 750 x 850 mm	1800 x 750 x 850 mm
Electrical Consumption	418 W	415 W	400 W
Freezer Temperature Control	-23°C ~ -7°C	-23°C ~ -7°C	-23°C ~ -7°C
Number of Shelves	4	4	6
Effective Capacity	307 L	420 L	502 L

Undercounter Low Drawer Freezer



MODEL	FTL-148MA-PD
Dimension WxDxH	1400 x 750 x 570 mm
Electrical Consumption	439 W
Freezer Temperature Control	-23°C ~ -7°C
Number of Drawers	4
Effective Capacity	176 L

Undercounter Door + Drawer Freezer



MODEL FT-126MA-P-3D

Dimension WxDxH	1200 x 600 x 850 mm
Electrical Consumption	410 W
Freezer Temperature Control	-23°C ~ -7°C
Number of Shelves	2
Number of Drawers	3
Effective Capacity	231 L



FT-156MA-P-3D

Dimension WxDxH	1500 x 600 x 850 mm
Electrical Consumption	415 W
Freezer Temperature Control	-23°C ~ -7°C
Number of Shelves	2
Number of Drawers	3
Effective Capacity	318 L



MODEL FT-186MA-P-3D

Dimension WxDxH	1800 x 600 x 850 mm
Electrical Consumption	400 W
Freezer Temperature Control	-23°C ~ -7°C
Number of Shelves	4
Number of Drawers	3
Effective Capacity	401 L



FT-128MA-P-3D

Dimension WxDxH	1200 x 750 x 850 mm
Electrical Consumption	418 W
Freezer Temperature Control	-23°C ~ -7°C
Number of Shelves	2
Number of Drawers	3
Effective Capacity	307 L



MODEL FT-158MA-P-3D

Dimension WxDxH	1500 x 750 x 850 mm
Electrical Consumption	415 W
Freezer Temperature Control	-23°C ~ -7°C
Number of Shelves	2
Number of Drawers	3
Effective Capacity	420 L



FT-188MA-P-3D

Dimension WxDxH	1800 x 750 x 850 mm
Electrical Consumption	400 W
Freezer Temperature Control	-23°C ~ -7°C
Number of Shelves	4
Number of Drawers	3
Effective Capacity	502 L

Category	Product Group	Model Name	Effective Capacity	No. of Compartments		Temperature Control	Electric Consumption	Product Dimension (mm)
				Shelves	Drawers			W x D x H
A-fit	Undercounter	RT-96MA-P	151 L	2	-	-6°C to 12°C	240 W	900 x 600 x 850
A-fit	Undercounter	RT-126MA-P	231 L	4	-	-6°C to 12°C	245 W	1200 x 600 x 850
A-fit	Undercounter	RT-156MA-P	318 L	4	-	-6°C to 12°C	245 W	1500 x 600 x 850
A-fit	Undercounter	RT-186MA-P	401 L	6	-	-6°C to 12°C	280 W	1800 x 600 x 850
A-fit	Undercounter	RT-216MA-P	490 L	6	-	-2°C to 12°C	318 W	2110 x 600 x 850
A-fit	Undercounter	RT-98MA-P	199 L	2	-	-6°C to 12°C	240 W	900 x 750 x 850
A-fit	Undercounter	RT-128MA-P	307 L	4	-	-6°C to 12°C	245 W	1200 x 750 x 850
A-fit	Undercounter	RT-158MA-P	420 L	4	-	-6°C to 12°C	245 W	1500 x 750 x 850
A-fit	Undercounter	RT-188MA-P	502 L	6	-	-6°C to 12°C	280 W	1800 x 750 x 850
A-fit	U/C Low Drawer	RTL-108MA-PD	85 L	-	2	-6°C to 12°C	234 W	980 x 750 x 570
A-fit	U/C Low Drawer	RTL-148MA-PD	176 L	-	4	-6°C to 12°C	250 W	1400 x 750 x 570
A-fit	U/C Low Drawer	RTL-188MA-PD	267 L	-	6	-6°C to 12°C	260 W	1820 x 750 x 570
A-fit	U/C Door + Drawer	RT-126MA-P-3D	231 L	2	3	-6°C to 12°C	245 W	1200 x 600 x 850
A-fit	U/C Door + Drawer	RT-156MA-P-3D	318 L	2	3	-6°C to 12°C	260 W	1500 x 600 x 850
A-fit	U/C Door + Drawer	RT-186MA-P-3D	401 L	4	3	-6°C to 12°C	280 W	1800 x 600 x 850
A-fit	U/C Door + Drawer	RT-128MA-P-3D	307 L	2	3	-6°C to 12°C	245 W	1200 x 750 x 850
A-fit	U/C Door + Drawer	RT-158MA-P-3D	420 L	2	3	-6°C to 12°C	260 W	1500 x 750 x 850
A-fit	U/C Door + Drawer	RT-188MA-P-3D	502 L	4	3	-6°C to 12°C	280 W	1800 x 750 x 850

Category	Product Group	Model Name	Effective Capacity	No. of Compartments		Temperature Control	Electric Consumption	Product Dimension (mm)
				Shelves	Drawers			W x D x H
A-fit	Undercounter	FT-96MA-P	151 L	2	-	-23°C to -7°C	415 W	900 x 600 x 850
A-fit	Undercounter	FT-126MA-P	231 L	4	-	-23°C to -7°C	410 W	1200 x 600 x 850
A-fit	Undercounter	FT-156MA-P	318 L	4	-	-23°C to -7°C	415 W	1500 x 600 x 850
A-fit	Undercounter	FT-186MA-P	401 L	6	-	-23°C to -7°C	400 W	1800 x 600 x 850
A-fit	Undercounter	FT-98MA-P	199 L	2	-	-23°C to -7°C	420 W	900 x 750 x 850
A-fit	Undercounter	FT-128MA-P	307 L	4	-	-23°C to -7°C	418 W	1200 x 750 x 850
A-fit	Undercounter	FT-158MA-P	420 L	4	-	-23°C to -7°C	415 W	1500 x 750 x 850
A-fit	Undercounter	FT-188MA-P	502 L	6	-	-23°C to -7°C	400 W	1800 x 750 x 850
A-fit	U/C Low Drawer	FTL-148MA-PD	176 L	-	4	-23°C to -7°C	439 W	1400 x 750 x 570
A-fit	U/C Door + Drawer	FT-126MA-P-3D	231 L	2	3	-23°C to -7°C	410 W	1200 x 600 x 850
A-fit	U/C Door + Drawer	FT-156MA-P-3D	318 L	2	3	-23°C to -7°C	415 W	1500 x 600 x 850
A-fit	U/C Door + Drawer	FT-186MA-P-3D	401 L	4	3	-23°C to -7°C	400 W	1800 x 600 x 850
A-fit	U/C Door + Drawer	FT-128MA-P-3D	307 L	2	3	-23°C to -7°C	418 W	1200 x 750 x 850
A-fit	U/C Door + Drawer	FT-158MA-P-3D	420 L	2	3	-23°C to -7°C	415 W	1500 x 750 x 850
A-fit	U/C Door + Drawer	FT-188MA-P-3D	502 L	4	3	-23°C to -7°C	400 W	1800 x 750 x 850

Upright Pillar-less Refrigerator



MODEL	HR-128MA-P-ML
Dimension WxDxH	1200 x 800 x 2050 mm
Electrical Consumption	411 W
Freezer Temperature Control	-6°C ~ 12°C
Number of Shelves	8
Effective Capacity	1053 L



MODEL	HR-148MA-P-ML
Dimension WxDxH	1400 x 800 x 2050 mm
Electrical Consumption	413 W
Freezer Temperature Control	-6°C ~ 12°C
Number of Shelves	8
Effective Capacity	1243 L

Upright Pillar-less Freezer



MODEL	HF-128MA-P-ML
Dimension WxDxH	1200 x 800 x 2050 mm
Electrical Consumption	453 W
Freezer Temperature Control	-23°C ~ -7°C
Number of Shelves	8
Effective Capacity	1053 L



MODEL	HF-148MA-P-ML
Dimension WxDxH	1400 x 800 x 2050 mm
Electrical Consumption	459 W
Freezer Temperature Control	-23°C ~ -7°C
Number of Shelves	8
Effective Capacity	1243 L

Undercounter Pillar-less Refrigerator



MODEL	RT-126MA-P-ML
Dimension WxDxH	1200 x 600 x 850 mm
Electrical Consumption	186 W
Chiller Temperature Control	-6°C ~ 12°C
Number of Shelves	4
Effective Capacity	231 L



MODEL	RT-156MA-P-ML
Dimension WxDxH	1500 x 600 x 850 mm
Electrical Consumption	189 W
Chiller Temperature Control	-6°C ~ 12°C
Number of Shelves	4
Effective Capacity	318 L



MODEL	RT-186MA-P-ML
Dimension WxDxH	1800 x 600 x 850 mm
Electrical Consumption	201 W
Chiller Temperature Control	-6°C ~ 12°C
Number of Shelves	6
Effective Capacity	401 L



MODEL	RT-128MA-P-ML
Dimension WxDxH	1200 x 750 x 850 mm
Electrical Consumption	186 W
Chiller Temperature Control	-6°C ~ 12°C
Number of Shelves	4
Effective Capacity	307 L



MODEL	RT-158MA-P-ML
Dimension WxDxH	1500 x 750 x 850 mm
Electrical Consumption	189 W
Freezer Temperature Control	-6°C ~ 12°C
Number of Shelves	4
Effective Capacity	420 L



MODEL	RT-188MA-P-ML
Dimension WxDxH	1800 x 750 x 850 mm
Electrical Consumption	201 W
Freezer Temperature Control	-6°C ~ 12°C
Number of Shelves	6
Effective Capacity	502 L

Undercounter Pillar-less Freezer



MODEL	FT-126MA-P-ML
Dimension WxDxH	1200 x 600 x 850 mm
Electrical Consumption	410 W
Freezer Temperature Control	-23°C ~ -7°C
Number of Shelves	4
Effective Capacity	231 L



MODEL	FT-156MA-P-ML
Dimension WxDxH	1500 x 600 x 850 mm
Electrical Consumption	415 W
Freezer Temperature Control	-23°C ~ -7°C
Number of Shelves	4
Effective Capacity	318 L



MODEL	FT-186MA-P-ML
Dimension WxDxH	1800 x 600 x 850 mm
Electrical Consumption	400 W
Freezer Temperature Control	-23°C ~ -7°C
Number of Shelves	6
Effective Capacity	401 L



MODEL	FT-128MA-P-ML	FT-158MA-P-ML	FT-188MA-P-ML
Dimension WxDxH	1200 x 750 x 850 mm	1500 x 750 x 850 mm	1800 x 750 x 850 mm
Electrical Consumption	418 W	415 W	400 W
Chiller Temperature Control	-23°C ~ -7°C	-23°C ~ -7°C	-23°C ~ -7°C
Number of Shelves	4	4	6
Effective Capacity	307 L	420 L	502 L

A-FIT PILLAR-LESS SPECIFICATIONS

Category	Product Group	Model Name	Effective Capacity	No. of Compartments		Temperature Control	Electric Consumption	Product Dimension (mm)
				Shelves	Drawers			W x D x H
A-fit	Upright (Pillar-less)	HR-128MA-P-ML	1053 L	8	-	-6°C to 12°C	411 W	1200 x 800 x 2050
A-fit	Upright (Pillar-less)	HR-148MA-P-ML	1243 L	8	-	-6°C to 12°C	413 W	1400 x 800 x 2050
A-fit	Upright (Pillar-less)	HF-128MA-P-ML	1053 L	8	-	-6°C to 12°C	453 W	1200 x 800 x 2050
A-fit	Upright (Pillar-less)	HF-148MA-P-ML	1243 L	8	-	-6°C to 12°C	459 W	1400 x 800 x 2050
A-fit	U/C (Pillar-less)	RT-126MA-P-ML	231 L	4	-	-6°C to 12°C	186 W	1200 x 600 x 850
A-fit	U/C (Pillar-less)	RT-156MA-P-ML	318 L	4	-	-6°C to 12°C	189 W	1500 x 600 x 850
A-fit	U/C (Pillar-less)	RT-186MA-P-ML	401 L	6	-	-6°C to 12°C	201 W	1800 x 600 x 850
A-fit	U/C (Pillar-less)	RT-128MA-P-ML	307 L	4	-	-6°C to 12°C	186 W	1200 x 750 x 850
A-fit	U/C (Pillar-less)	RT-158MA-P-ML	420 L	4	-	-6°C to 12°C	189 W	1500 x 750 x 850
A-fit	U/C (Pillar-less)	RT-188MA-P-ML	502 L	6	-	-6°C to 12°C	201 W	1800 x 750 x 850
A-fit	U/C (Pillar-less)	FT-126MA-P-ML	231 L	-	4	-23°C to -7°C	410 W	1200 x 600 x 850
A-fit	U/C (Pillar-less)	FT-156MA-P-ML	318 L	-	4	-23°C to -7°C	415 W	1500 x 600 x 850
A-fit	U/C (Pillar-less)	FT-186MA-P-ML	401 L	-	6	-23°C to -7°C	400 W	1800 x 600 x 850
A-fit	U/C (Pillar-less)	FT-128MA-P-ML	307 L	-	4	-23°C to -7°C	418 W	1200 x 750 x 850
A-fit	U/C (Pillar-less)	FT-158MA-P-ML	420 L	-	4	-23°C to -7°C	415 W	1500 x 750 x 850
A-fit	U/C (Pillar-less)	FT-188MA-P-ML	502 L	-	6	-23°C to -7°C	400 W	1800 x 750 x 850

Upright
Heated Swing Glass Door
Refrigerator



MODEL	HR-78MA-PG	HR-128MA-PG
Dimension WxDxH	700 x 800 x 2050 mm	1200 x 800 x 2050 mm
Electrical Consumption	463 W	539 W
Temperature Control	-2°C ~ 12°C	-2°C ~ 12°C
Number of Shelves	4	8
Effective Capacity	569 L	1053 L



MODEL	HR-148MA-PG	HR-188MA-PG
Dimension WxDxH	1400 x 800 x 2050 mm	1800 x 800 x 2050 mm
Electrical Consumption	565 W	623 W
Temperature Control	-2°C ~ 12°C	-2°C ~ 12°C
Number of Shelves	8	12
Effective Capacity	1243 L	1632 L



MODEL	HR-76MA-PG	HR-126MA-PG
Dimension WxDxH	700 x 650 x 2050 mm	1200 x 650 x 2050 mm
Electrical Consumption	463 W	539 W
Temperature Control	-2°C ~ 12°C	-2°C ~ 12°C
Number of Shelves	4	8
Effective Capacity	467 L	866 L



MODEL HR-146MA-PG

Dimension WxDxH	1400 x 650 x 2050 mm
Electrical Consumption	565 W
Chiller Temperature Control	-2°C ~ 12°C
Number of Shelves	8
Effective Capacity	1021 L

**Undercounter
Sliding Glass Door
Refrigerator**



MODEL RT-126MA-PSG

Dimension WxDxH	1200 x 600 x 850 mm
Electrical Consumption	292 W
Chiller Temperature Control	-2°C ~ 12°C
Number of Shelves	4
Effective Capacity	231 L



MODEL RT-156MA-PSG

Dimension WxDxH	1500 x 600 x 850 mm
Electrical Consumption	249 W
Chiller Temperature Control	-2°C ~ 12°C
Number of Shelves	4
Effective Capacity	318 L



MODEL RT-158MA-PSG

Dimension WxDxH	1500 x 750 x 850 mm
Electrical Consumption	249 W
Chiller Temperature Control	-2°C ~ 12°C
Number of Shelves	4
Effective Capacity	420 L

**Upright
Heated Long Glass Door
Refrigerator**



MODEL HR-76MA-PLG

Dimension WxDxH	700 x 650 x 2050 mm
Electrical Consumption	463 W
Chiller Temperature Control	-2°C ~ 12°C
Number of Shelves	4
Effective Capacity	467 L



MODEL HR-126MA-PLG

Dimension WxDxH	1200 x 650 x 2050 mm
Electrical Consumption	539 W
Chiller Temperature Control	-2°C ~ 12°C
Number of Shelves	8
Effective Capacity	866 L



MODEL HR-78MA-PLG

Dimension WxDxH	700 x 800 x 2050 mm
Electrical Consumption	463 W
Chiller Temperature Control	-2°C ~ 12°C
Number of Shelves	4
Effective Capacity	569 L



MODEL HR-128MA-PLG

Dimension WxDxH	1200 x 800 x 2050 mm
Electrical Consumption	539 W
Chiller Temperature Control	-2°C ~ 12°C
Number of Shelves	8
Effective Capacity	1053 L

**Undercounter
Heated Swing Glass Door
Refrigerator**



MODEL RT-96MA-PG

Dimension WxDxH	900 x 600 x 850 mm
Electrical Consumption	201 W
Temperature Control	-2°C ~ 12°C
Number of Shelves	2
Effective Capacity	151 L



MODEL RT-126MA-PG

Dimension WxDxH	1200 x 600 x 850 mm
Electrical Consumption	229 W
Temperature Control	-2°C ~ 12°C
Number of Shelves	4
Effective Capacity	231 L


MODEL RT-156MA-PG

Dimension WxDxH	1500 x 600 x 850 mm
Electrical Consumption	241 W
Temperature Control	-2°C ~ 12°C
Number of Shelves	4
Effective Capacity	318 L


MODEL RT-186MA-PG

Dimension WxDxH	1800 x 600 x 850 mm
Electrical Consumption	264 W
Temperature Control	-2°C ~ 12°C
Number of Shelves	6
Effective Capacity	401 L


MODEL RT-98MA-PG

Dimension WxDxH	900 x 750 x 850
Electrical Consumption	201 W
Temperature Control	-2°C ~ 12°C
Number of Shelves	2
Effective Capacity	199 L


MODEL RT-128MA-PG

Dimension WxDxH	1200 x 750 x 850 mm
Electrical Consumption	224 W
Temperature Control	-2°C ~ 12°C
Number of Shelves	4
Effective Capacity	307 L


MODEL RT-158MA-PG

Dimension WxDxH	1500 x 750 x 850 mm
Electrical Consumption	241 W
Temperature Control	-2°C ~ 12°C
Number of Shelves	4
Effective Capacity	420 L


MODEL RT-188MA-PG

Dimension WxDxH	1800 x 750 x 850 mm
Electrical Consumption	264 W
Temperature Control	-2°C ~ 12°C
Number of Shelves	6
Effective Capacity	502 L

Prep Table


MODEL RT-128MA-P-PR

Dimension WxDxH	1200 x 750 x 850 mm
Electrical Consumption	165 W
Temperature Control	-2°C ~ 12°C
Number of Shelves	4
Effective Capacity	304 L

Prep Table (Cover + Cutting Board)


MODEL RT-128MA-P-PRS

Dimension WxDxH	1200 x 750 x 1076 mm
Electrical Consumption	81 W
Temperature Control	-2°C ~ 12°C
Number of Shelves	4
Effective Capacity	304 L


MODEL RT-158MA-P-PRS

Dimension WxDxH	1500 x 750 x 1100 mm
Electrical Consumption	84 W
Temperature Control	-2°C ~ 12°C
Number of Shelves	4
Effective Capacity	410 L


MODEL RT-188MA-P-PRS

Dimension WxDxH	1800 x 750 x 1100 mm
Electrical Consumption	96 W
Temperature Control	-2°C ~ 12°C
Number of Shelves	6
Effective Capacity	517 L

A-FIT GLASS DOOR SPECIFICATIONS

Category	Product Group	Model Name	Effective Capacity	No. of Shelves	Temperature Control	Electric Consumption	Product Dimension (mm)
							W x D x H
A-fit	Upright (Swing Glass Door)	HR-78MA-PG	569 L	4	-2°C to 12°C	463 W	700 x 800 x 2050
A-fit	Upright (Swing Glass Door)	HR-128MA-PG	1053 L	8	-2°C to 12°C	539 W	1200 x 800 x 2050
A-fit	Upright (Swing Glass Door)	HR-148MA-PG	1243 L	8	-2°C to 12°C	565 W	1400 x 800 x 2050
A-fit	Upright (Swing Glass Door)	HR-188MA-PG	1632 L	12	-2°C to 12°C	623 W	1800 x 800 x 2050
A-fit	Upright (Swing Glass Door)	HR-76MA-PG	467 L	4	-2°C to 12°C	467 W	700 x 650 x 2050
A-fit	Upright (Swing Glass Door)	HR-126MA-PG	866 L	8	-2°C to 12°C	539 W	1200 x 650 x 2050
A-fit	Upright (Swing Glass Door)	HR-146MA-PG	1021 L	8	-2°C to 12°C	565 W	1400 x 650 x 2050
A-fit	U/C (Sliding Glass Door)	RT-126MA-PSG	231 L	4	-2°C to 12°C	192 W	1200 x 600 x 850
A-fit	U/C (Sliding Glass Door)	RT-156MA-PSG	318 L	4	-2°C to 12°C	249 W	1500 x 600 x 850
A-fit	U/C (Sliding Glass Door)	RT-158MA-PSG	420 L	4	-2°C to 12°C	249 W	1500 x 750 x 850
A-fit	Upright (Long Glass Door)	HR-76MA-PLG	467 L	4	-2°C to 12°C	463 W	700 x 650 x 2050
A-fit	Upright (Long Glass Door)	HR-126MA-PLG	866 L	8	-2°C to 14°C	539 W	1200 x 650 x 2050
A-fit	Upright (Long Glass Door)	HR-78MA-PLG	569 L	4	-2°C to 13°C	463 W	700 x 800 x 2050
A-fit	Upright (Long Glass Door)	HR-128MA-PLG	1053 L	8	-2°C to 15°C	539 W	1200 x 800 x 2050
A-fit	U/C (Swing Glass Door)	RT-96MA-PG	151 L	2	-2°C to 12°C	201 W	900 x 600 x 850
A-fit	U/C (Swing Glass Door)	RT-126MA-PG	231 L	4	-2°C to 12°C	229 W	1200 x 600 x 850
A-fit	U/C (Swing Glass Door)	RT-156MA-PG	318 L	4	-2°C to 12°C	241 W	1500 x 600 x 850
A-fit	U/C (Swing Glass Door)	RT-186MA-PG	401 L	6	-2°C to 12°C	264 W	1800 x 600 x 850
A-fit	U/C (Swing Glass Door)	RT-98MA-PG	199 L	2	-2°C to 12°C	201 W	900 x 750 x 850
A-fit	U/C (Swing Glass Door)	RT-128MA-PG	307 L	4	-2°C to 12°C	224 W	1200 x 750 x 850
A-fit	U/C (Swing Glass Door)	RT-158MA-PG	420 L	4	-2°C to 12°C	241 W	1500 x 750 x 850
A-fit	U/C (Swing Glass Door)	RT-188MA-PG	502 L	6	-2°C to 12°C	264 W	1800 x 750 x 850

A-FIT PREP TABLE SPECIFICATIONS

Category	Product Group	Model Name	Effective Capacity	No. of Shelves	Temperature Control	Electric Consumption	Product Dimension (mm)
							W x D x H
A-fit	Prep Table	RT-128MA-P-PR	304 L	4	-2°C to 12°C	165 W	1200 x 750 x 850
A-fit	Prep Table (Cover + Cutting Board)	RT-128MA-P-PRS	304 L	4	-2°C to 12°C	81 W	1200 x 750 x 1076
A-fit	Prep Table (Cover + Cutting Board)	RT-158MA-P-PRS	410 L	4	-2°C to 12°C	84 W	1500 x 750 x 1100
A-fit	Prep Table (Cover + Cutting Board)	RT-188MA-P-PRS	517 L	6	-2°C to 12°C	96 W	1800 x 750 x 1100

GOLDLINE MODEL

Undercounter Drawer Refrigerator Depth 600mm



MODEL

RTC-125DNA-GN-6D

RTC-167DNA-GN-9D

Dimension **WxDxH**
Electrical Consumption
Temperature Control
Number of Drawers
Effective Capacity

1250 x 600 x 850 mm
315 W
-6°C ~ 12°C
6
218 L

1670 x 600 x 850 mm
315 W
-6°C ~ 12°C
9
324 L

Undercounter Drawer Refrigerator Depth 750mm



MODEL

RTC-90DDA-GN-2D

RTC-90DDA-GN-3D

RTC-125DDA-GN-4D

Dimension **WxDxH (+Leg)**
Electrical Consumption
Temperature Control
Number of Drawers
Effective Capacity

900 x 750 x 850 mm
225 W
-6°C ~ 12°C
2
176 L

900 x 750 x 850 mm
225 W
-6°C ~ 12°C
3
176 L

1250 x 750 x 850 mm
315 W
-6°C ~ 12°C
4
296 L

Undercounter Drawer Refrigerator Depth 750mm



MODEL

RTC-125DDA-GN-6D

RTC-167DDA-GN-6D

RTC-167DDA-GN-9D

Dimension **WxDxH (+Leg)**
Electrical Consumption
Temperature Control
Number of Drawers
Effective Capacity

1250 x 750 x 850 mm
315 W
-6°C ~ 12°C
6
296 L

1670 x 750 x 850 mm
315 W
-6°C ~ 12°C
6
443 L

1670 x 750 x 850 mm
315 W
-6°C ~ 12°C
9
443 L

Undercounter Drawer Freezer Depth 600mm



MODEL	FTC-125DNA-GN-6D	FTC-167DNA-GN-9D
Dimension WxDxH (+Leg)	1250 x 600 x 850 mm	1670 x 600 x 850 mm
Electrical Consumption	560 W	619 W
Temperature Control	-25°C ~ -7°C	-25°C ~ -7°C
Number of Drawers	6	9
Effective Capacity	218 L	324 L

Undercounter Drawer Freezer Depth 750mm



MODEL	FTC-90DDA-GN-2D	FTC-90DDA-GN-3D	FTC-125DDA-GN-4D
Dimension WxDxH (+Leg)	900 x 750 x 850 mm	900 x 750 x 850 mm	1250 x 750 x 850 mm
Electrical Consumption	225 W	225 W	560 W
Temperature Control	-25°C ~ -7°C	-25°C ~ -7°C	-25°C ~ -7°C
Number of Drawers	2	3	4
Effective Capacity	176 L	176 L	296 L

Undercounter Drawer Freezer Depth 750mm



MODEL	FTC-125DDA-GN-6D	FTC-167DNA-GN-6D	FTC-167DDA-GN-9D
Dimension WxDxH (+Leg)	1250 x 750 x 850 mm	1670 x 750 x 850 mm	1670 x 750 x 850 mm
Electrical Consumption	560 W	619 W	619 W
Temperature Control	-25°C ~ -7°C	-25°C ~ -7°C	-25°C ~ -7°C
Number of Drawers	6	6	9
Effective Capacity	296 L	443 L	443 L

Category	Product Group	Model Name	Effective Capacity	No. of Drawers	Temperature Control	Electric Consumption	Product Dimension (mm) W x D x H
Goldline	Undercounter Drawer Refrigerator Depth 600mm	RTC-125DNA-GN-6D	218 L	6	-6°C to 12°C	315 W	1250 x 600 x 850
Goldline		RTC-167DNA-GN-9D	324 L	9	-6°C to 12°C	315 W	1670 x 600 x 850
Goldline	Undercounter Drawer Refrigerator Depth 750mm	RTC-90DDA-GN-2D	176 L	2	-6°C to 12°C	225 W	900 x 750 x 850
Goldline		RTC-90DDA-GN-3D	176 L	3	-6°C to 12°C	225 W	900 x 750 x 850
Goldline		RTC-125DDA-GN-4D	296 L	4	-6°C to 12°C	315 W	1250 x 750 x 850
Goldline		RTC-125DDA-GN-6D	296 L	6	-6°C to 12°C	315 W	1250 x 750 x 850
Goldline		RTC-167DDA-GN-6D	443 L	6	-6°C to 12°C	315 W	1670 x 750 x 850
Goldline		RTC-167DDA-GN-9D	443 L	9	-6°C to 12°C	315 W	1670 x 750 x 850
Goldline	Undercounter Drawer Freezer Depth 600mm	FTC-125DNA-GN-6D	218 L	6	-25°C to -7°C	560 W	1250 x 600 x 850
Goldline		FTC-167DNA-GN-9D	324 L	9	-25°C to -7°C	619 W	1670 x 600 x 850
Goldline	Undercounter Drawer Freezer Depth 750mm	FTC-90DDA-GN-2D	176 L	2	-25°C to -7°C	225 W	900 x 750 x 850
Goldline		FTC-90DDA-GN-3D	176 L	3	-25°C to -7°C	225 W	900 x 750 x 850
Goldline		FTC-125DDA-GN-4D	296 L	4	-25°C to -7°C	560 W	1250 x 750 x 850
Goldline		FTC-125DDA-GN-6D	296 L	6	-25°C to -7°C	560 W	1250 x 750 x 850
Goldline		FTC-167DNA-GN-6D	443 L	6	-25°C to -7°C	619 W	1670 x 750 x 850
Goldline		FTC-167DDA-GN-9D	443 L	9	-25°C to -7°C	619 W	1670 x 750 x 850

DEEP FREEZER

 Natural refrigerant

Keeping food at an ultra-low temperature of -60°C suppresses enzymatic decomposition of proteins and oxidation of fats. It also prevents discoloration and deterioration of texture caused by freezer burn. With ultra-low temperature deep freezer, quality of food is assured for your customers to enjoy their feast.



MODEL	HDF-140A 	HDF-300A 	HDF-400A 
Dimension WxDxH	725 x 693 x 875 mm	1265 x 710 x 875 mm	1565 x 710 x 875 mm
Electrical Consumption	255 W	320 W	355 W
Temperature Control (approx.)	-60°C ~ -50°C	-60°C ~ -50°C	-60°C ~ -50°C
Effective Capacity	140 L	298 L	385 L
Refrigerant	R600, R1150	R600, R1150	R600, R1150

DEEP FREEZER SPECIFICATIONS

Category	Model Name	Effective Capacity	Temperature Control	Electric Consumption	Product Dimension (mm)
					W x D x H
 Deep Freezer	HDF-140A	140 L	-60°C ~ -50°C	255 W	725 x 693 x 875
 Deep Freezer	HDF-300A	298 L	-60°C ~ -50°C	320 W	1265 x 710 x 875
 Deep Freezer	HDF-400A	385 L	-60°C ~ -50°C	355 W	1565 x 710 x 875

DISHWASHER

Hoshizaki introduces the high performance and low water consumption efficient dishwashing solution for your busy kitchen. Simple and compact in size, our dishwasher is designed to take the load off your operations with an easy to operate unit for small to medium size establishments.



Hood

Sheet Pan

MODEL	HW-600B3	HW-600B
Dimension WxDxH (Door Opening)	707 x 779 x 1485 (1948) mm	707 x 779 x 1485 (1948) mm
Electrical Consumption	9.7 kW	3.4 kW
Washing Capacity Racks per Hour	69 / 35 / 27 / 23 / 18	69 / 35 / 27 / 23 / 18
Water Consumption Per Rack	2.3 L	2.3 L
Power supply	3phase 380V / 60Hz	1phase 220V / 60Hz
Max Noise	67 dBA	67 dBA

DISHWASHER

Hood



MODEL OBM 1080T

MODEL OBM 1080T

MODEL HW-320B

Dimension **WxDxH (Door Opening)** 700 x 785 x 1480 (1960) mm
 Electrical Consumption 9.7 kW
 Washing Capacity **Racks per Hour** 69 / 35 / 27 / 23 / 18
 Water Consumption **Per Rack** 2.8 L
 Power supply 3phase 220V / 60Hz
 Max Noise 75 dBA

Dimension **WxDxH (Door Opening)** 700 x 785 x 1480 (1960) mm
 Electrical Consumption 3.4 Kw
 Washing Capacity **Racks per Hour** 69 / 35 / 27 / 23 / 18
 Water Consumption **Per Rack** 2.8 L
 Power supply 1 phase 220V / 60Hz
 Max Noise 75 dBA

Dimension **WxDxH (Door Opening)** 600 x 655 x 830 mm
 Electrical Consumption 3.4 kW
 Washing Capacity **Racks per Hour** 35 / 27/ 23 / 20 / 18
 Water Consumption **Per Rack** 2.3 L
 Power supply 1 phase 220V / 60Hz
 Max Noise 65 dBA



MODEL HW-320B-S

MODEL OBY 50T

Dimension **WxDxH** 595 x 645 x 830 mm
 Electrical Consumption 5.2 kW
 Washing Capacity **Racks per Hour** 35 / 27 / 23 / 20 / 18
 Water Consumption **Per Rack** 2.3 L
 Power supply 1phase 220V / 60Hz
 Max Noise 70 dBA

Dimension **WxDxH** 595 x 645 x 830 mm
 Electrical Consumption 5.3 kW
 Washing Capacity **Racks per Hour** 35 / 27 / 23 / 20 / 18
 Water Consumption **Per Rack** 2.8 L
 Power supply 1phase 220V / 60Hz
 Max Noise 70 dBA

DISHWASHER SPECIFICATIONS

Category	Product Group	Model Name	Temperature Control		Water Consumption Per Rack	Electric Consumption	Maximum Noise	Product Dimension (mm) W x D x H
			Washing (°C)	Rinsing (°C)				
Dishwasher	Hood	HW-600B3	55 - 60	80 - 85	2.3 L	9.7 kW	67dBA	707 x 779 x 1485(1948)
Dishwasher	Hood	HW-600B	55 - 60	80 - 85	2.3 L	3.4 kW	67dBA	707 x 779 x 1485 (1948)
Dishwasher	Hood	OBM 1080T	55 - 60	80 - 85	2.8 L	9.7 kW	75dBA	700 x 785 x 1480 (1960)
Dishwasher	Hood	OBM 1080T	55 - 60	80 - 85	2.8 L	3.4 kW	75dBA	700 x 785 x 1480 (1960)
Dishwasher	Undercounter	HW-320B	55 - 60	80 - 85	2.3 L	3.4 kW	65dBA	600 x 655 x 830
Dishwasher	Undercounter	HW-320B-S	55 - 60	80 - 85	2.3 L	5.2 kW	70dBA	595 x 645 x 830
Dishwasher	Undercounter	OBY 50T	55 - 60	80 - 85	2.8 L	5.3 kW	70dBA	595 x 645 x 830

Drain pump (T), Rinsing Pump (R), Detergent pump (D), Rinse aid pump (P) are optional parts.

BEER DISPENSER



Automatic draft beer dispenser

beer dispenser



MODEL DBF-AS65WE-T

MODEL DBF-40SAC

Dimension **WxDxH** 367 x 674 x 764 mm
 Electric Consumption 345 W
 Dispensing Capacity 65L (30°C - 8°C 4H)
 Power Supply 1phase 220-240V, 50/60Hz

Dimension **WxDxH** 330 x 646 x 510 mm
 Electric Consumption 250W
 Dispensing Capacity 330 x 646 x 510 mm
 Power Supply 1 phase 220V, 60Hz

BEER DISPENSER SPECIFICATIONS

Category	Product Group	Model Name	Power Supply	Electric Consumption	Dispensing Capacity	Product Dimension (mm) W x D x H
Beer Dispenser	Automatic Draft Beer Dispenser	DBF-AS65WE-T	1phase 220-240V, 50/60Hz	345 W	65L (30°C - 8°C 4H)	367 x 674 x 764 mm
Beer Dispenser	Beer Dispenser	DBF-40SAC	1 phase 220V, 60Hz	250 W	40L (30°C8°C 4H)	330 x 646 x 510 mm